



63752

LIFTING POINTS & SHACKLES

Material

Forged alloy steel, black oxide coated.

Technical Notes

Supplied with thin head bolt, nut and

cotter pin.

Tips

Min. design safety factor 6:1.

Important Notes

All dimensions in imperial.

Order No.	Working load lb	d ₁	d ₂	d ₃	l ₁	l ₂	w ₁	w ₂	w ₃	w ₄	w ₅
63752.W0371I	2000	3/8	1.03	0.44	2.49	1.44	1.78	0.91	0.38	0.66	2.17
63752.W0431I	3000	7/16	1.16	0.50	2.91	1.69	2.03	1.06	0.44	0.75	2.51
63752.W0501I	4000	1/2	1.31	0.63	3.28	1.88	2.31	1.19	0.50	0.81	2.80
63752.W0631I	6500	5/8	1.69	0.75	4.19	2.38	2.94	1.50	0.63	1.06	3.53
63752.W0881I	13000	7/8	2.28	1.00	5.83	3.31	4.03	2.09	0.88	1.44	4.71
63752.W1141I	19000	1-1/8	2.91	1.25	7.47	4.25	5.16	2.69	1.13	1.81	6.00
63752.W1251I	24000	1-1/4	3.25	1.38	8.25	4.69	5.75	3.00	1.25	2.03	6.51