



## 63621

LIFTING POINTS & SHACKLES

### Material

Forged chrome moly steel, heat treated and black oxide coated.

### Technical Notes

Magnaflux tested for ASTM 1444.

### Tips

Min. design safety factor 6:1. 180° pivot under load.

Always follow safety instructions.

### Important Notes

All dimensions in imperial.

Order No.	Type	Rated load lb	$d_1$	$r_1$	$l_1$	$d_2$	$w_1$	Weight lb
63621.W0311I	One	2000	5/16 (x2)	1/2	2	1-3/4	2-1/2	0.58
63621.W0371I	One	2500	3/8 (x2)	5/8	2-1/2	2-1/4	3-3/16	1.07
63621.W0501I	One	5000	1/2 (x2)	3/4	3	2-5/8	3-7/8	2.06
63621.W0502I	Two	12000	1/2 (x4)	7/8	4	3-1/8	5-1/4	4.10
63621.W0631I	Two	20000	5/8 (x4)	1	5	3-5/8	6-3/16	7.94

  

Order No.	$w_2$	$w_3$	$w_4$	$w_5$	tl ft·lb	Screw thread	Screw length
63621.W0311I	3/4	5/16	1	0	4-7	5/16-18	1-1/4
63621.W0371I	7/8	3/8	1-1/8	0	7-10	3/8-16	1-1/4
63621.W0501I	1-1/8	1/2	1-1/2	0	20-25	1/2-13	2
63621.W0502I	1-3/8	3/4	1-5/8	1-1/4	20-25	1/2-13	2-1/4
63621.W0631I	1-7/8	1	2-1/16	1-1/4	42-50	5/8-11	2-3/4