



Material

Body & Handle: die cast zinc, black powder coated.

Cylinder lock: die cast zinc, chrome plated. Rod Control Mechanism: die cast zinc. Supplied with: Keys: two per lock. Not supplied: Cam: order separately.

Technical Notes

Please note that the two point latching models use a bespoke mechanism. A cam

cannot be fitted to it to create a three point latching.

Order cam separately.

Cams: see suitable cam A0215. Select "without projection" cam type. Dimensions ch and cl relate to cam. Use formula to calculate ch (required cam offset), and refer to cam selection chart; **ch = h - lh** where;

ch = required cam off-set/height.

h = grip length (distance between inside of latch face and front of cam). lh = body length of cam latch/lock to be

used (see product table below). Rods & Guides: to achieve 3-point latching - A0303, A0321, A0325.

Tips

Suitable for panel thickness 1-4mm. For indoor or outdoor use. For use inside or outside gasket.

Order No.	Finish	Latching type	Key type	Button	1	w	lh	а	b	dm stroke
B2380.AW0010	Black Coated	3	Keyed Alike	W/o	133	36	22	122	196	15
B2380.AW0020	Black Coated	3	Keyed Alike	With	133	36	22	122	196	15
B2380.AW0030	Black Coated	2	Keyed Alike	W/o	133	36	22	122	196	15
B2380.AW0040	Black Coated	2	Keyed Alike	With	133	36	22	122	196	15

